

IB - In-Frame Boxes - Aluminum Single Top Open Lid

In-Frame boxes are super heavy duty, high capacity and offer easy access from back of the truck. Boxes are available with Padlock or T-Handle Lock. Boxes are perfect for standing on when changing trailer connections or a perfect way to store your equipment, like chains, binders, straps, or your personal gear. In-Frame boxes are available in different sizes, ranging from 12" to 48" or can be ordered in custom size. All AMERICAN TRUCKBOXES boxes are designed and built to keep your equipment safe and secure.


Description

- An engineered aluminum construction
- Fully seam welded on all seams and corners
- Stainless steel continuous hinge on full length of lid
- Channel brace reinforced lid serves as a platform
- Pad lockable adjustable latch or SS Dolphin Tail T-handle latch
- Optional SS T-handle cover – 1A060-C1
- Automotive type weather seal
- Batteries – Boxes are available to install batteries – SPECIAL ORDER
- Mounting kit included: (Kits Av.= M3100F)

A-IB51 = Pad Lock



A-IB52 = DT-T-Handle



Note: Box door is available in: Standard = Smooth (S) or for Diamond Tread (T) and Mirror (M) - change end of part number.

No.	Model Number	Material	Lock	Height (in.)	Depth (in.)	Width (in.)	Dim "A" (in)	Notch H" x W"	Door Opening Depth (in.)	Door Opening Width (in.)	Weight (lb.)
1.	A-IB51-81824-T	.125 Smooth/.125 TP	Padlock	8	18	24	5-3/8	N/A	10	19-1/2	30
2.	A-IB51-82424-T	.125 Smooth/.125 TP	Padlock	8	24	24	5-3/8	N/A	16	19-1/2	36
3.	A-IB51-102224-T	.125 Smooth/.125 TP	Padlock	10	22	24	7-3/8	N/A	14	19-1/2	36
4.	A-IB51-103624-T	.125 Smooth/.125 TP	Padlock	10	36	24	7-3/8	N/A	28	19-1/2	52
5.	A-IB51-131824N-T	.125 Smooth/.125 TP	Padlock	13	18	24	10-3/8	4 x 6	10	19-1/2	51
6.	A-IB51-132424N-T	.125 Smooth/.125 TP	Padlock	13	24	24	10-3/8	4 x 6	16	19-1/2	57
7.	A-IB52-81824-T	.125 Smooth/.125 TP	T-Handle	8	18	24	5-3/8	N/A	10	19-1/2	30
8.	A-IB52-82424-T	.125 Smooth/.125 TP	T-Handle	8	24	24	5-3/8	N/A	16	19-1/2	36
9.	A-IB52-102224-T	.125 Smooth/.125 TP	T-Handle	10	22	24	7-3/8	N/A	14	19-1/2	36
10.	A-IB52-103624-T	.125 Smooth/.125 TP	T-Handle	10	36	24	7-3/8	N/A	28	19-1/2	52
11.	A-IB52-131824N-T	.125 Smooth/.125 TP	T-Handle	13	18	24	10-3/8	4 x 6	10	19-1/2	51
12.	A-IB52-132424N-T	.125 Smooth/.125 TP	T-Handle	13	24	24	10-3/8	4 x 6	16	19-1/2	57