

L-CB Series = Steel Cross Beams for M2100 Series Brackets.

Cross beams are super heavy duty, and mounted between the 2100 series L-brackers. Cross beam supports the bottom of box when heavy objects are loaded into box. All ATB mounting kits are designed and built to keep your boxes safe and secure.

Description

- An engineered 1.5" x 3.0" .187 (3/16g) steel
- Zinc epoxy primer with MR powder baked topcoat finish ensures years dependability
- An engineered 1.5" x 3.0" .250 (1/4g) aluminum
- Predrilled 1/2" holes for easy mounting

| | Part | | | | Load |
|-----|---------|-----------------|------------------|-----------|--------------|
| No. | Number | Application | Length | Weight | Rating |
| 1. | L-CB24A | Alum Under Box | 24" – 16 5/8" | 2.2 lbs. | 500 lbs. Max |
| 2. | L-CB30A | Alum Under Box | 30" – 22-5/8" | 2.8 lbs. | 500 lbs. Max |
| 3. | L-CB36A | Alum Under Box | 36" – 28-5/8" | 3.5 lbs. | 500 lbs. Max |
| 4. | L-CB48A | Alum Under Box | 48" – 40-5/8" | 4.8 lbs. | 500 lbs. Max |
| 5. | L-CB60A | Alum Under Box | 60" – 52-5/8" | 6.4 lbs. | 500 lbs. Max |
| 6. | L-CB72A | Alum Under Box | 72" – 64-5/8" | 7.8 lbs. | 500 lbs. Max |
| 7. | L-CB24S | Steel Under Box | 24" – 16 5/8" | 4.8 lbs. | 500 lbs. Max |
| 8. | L-CB30S | Steel Under Box | 30" $-22-5/8$ " | 6.0 lbs. | 500 lbs. Max |
| 9. | L-CB36S | Steel Under Box | 36" $-28-5/8$ " | 7.5 lbs. | 500 lbs. Max |
| 10. | L-CB48S | Steel Under Box | 48" $-40-5/8$ " | 10.5 lbs. | 500 lbs. Max |
| 11. | L-CB60S | Steel Under Box | 60" – $52-5/8$ " | 14.0 lbs. | 500 lbs. Max |
| 12. | L-CB72S | Steel Under Box | 72" – 64-5/8" | 17.0 lbs. | 500 lbs. Max |
| | | | | | |



M2450D Series = Aluminum Underbody Top Mount Application

Adjustable under deck top mount brackets are heavy duty, and mounted to box and under van cross beam applications. All ATB mounting kits are designed and built to keep your boxes safe and secure. (See Mounting Kit Installation Sheet for more information)

Description

- An engineered .190 (7g) Aluminum Construction
- Predrilled holes adjustable for easy mounting

| | Part | | Height | Weight | Load |
|-----|----------------|-------------|------------|---------|--------------|
| No. | Number | Application | Width | Per Set | Rating |
| 1. | M2450UD-6-18B | Under Deck | 6"x 15.5" | 13 lbs. | 250 lbs. Max |
| 2. | M2450UD-6-20B | Under Deck | 6"x 17.5" | 14 lbs. | 250 lbs. Max |
| 3. | M2450UD-6-22B | Under Deck | 6"x 19.5" | 15 lbs. | 250 lbs. Max |
| 4. | M2450UD-6-24B | Under Deck | 6"x 21.5" | 16 lbs. | 250 lbs. Max |
| 5. | M2450UD-12-18B | Under Deck | 12"x 15.5" | 20 lbs. | 250 lbs. Max |
| 6. | M2450UD-12-20B | Under Deck | 12"x 17.5" | 12 lbs. | 250 lbs. Max |
| 7. | M2450UD-12-22B | Under Deck | 12"x 19.5" | 24 lbs. | 250 lbs. Max |
| 8. | M2450UD-12-24B | Under Deck | 12"x 21.5" | 26 lbs. | 250 lbs. Max |

